

6,8 mm REM. SPC

FMJ ^{110 GRS} SB68C



Full Metal Jacket bullet. Standard lead core with a metallic jacket. Best for training and target shooting applications.



PROPERTIES

BULLET	TYPE		FMJ
	WEIGHT	grs	110
	DIAMETER	in	0.277
	SECTIONAL DENSITY	lb/in ²	0.205
	MATERIAL OF JACKET		CuZn 10
BALLISTIC COEFFICIENT		G1	0.307
		G7	0.155
CARTRIDGE	LENGTH	in	2.244
POWER FACTOR ESTIMATED		kgr-fps	281.2
TEST BARREL LENGTH		in	16¼
SUGGESTED USE			Range, Match/Competition
FEATURES			Reliable Functioning, Non-expanding, No Barrel Leading

PACKAGING

BOXES PER CASE	50
WEIGHT PER CASE	lb 39.7

BALLISTICS

DISTANCE	y	MUZZLE	100	200	300	400
VELOCITY	fps	2,556	2,275	2,013	1,767	1,536
ENERGY	ft-lb	1,595	1,264	989	763	576
DISTANCE	y	50	100	200	300	400
POINTS OF IMPACT	in	-0.3	0.0	-4.8	-18.1	-42.7

