

6,5 × 55 SE

HPBT

V341622
142 GRS



Designed for sport shooting. Hollow Point Boat-Tail bullets are the finest in accuracy and consistency.



PROPERTIES

| | | | |
|-------------------------------|--------------------|--------------------|---------|
| BULLET | TYPE | | HPBT |
| | WEIGHT | grs | 142 |
| | DIAMETER | in | 0.264 |
| | SECTIONAL DENSITY | lb/in ² | 0.291 |
| | MATERIAL OF JACKET | | CuZn 10 |
| BALLISTIC COEFFICIENT | | G1 | 0.525 |
| | | G7 | 0.264 |
| RIFLE TWIST | | | 8,5" |
| PRIMER | TYPE | | N/A |
| | STYLE | | N/A |
| CARTRIDGE | LENGTH | in | 3.110 |
| POWER FACTOR ESTIMATED | | kgr fps | 350.3 |
| TEST BARREL LENGTH | | in | 23½ |
| SUGGESTED USE | | | N/A |
| FEATURES | | | N/A |

PACKAGING

| | | |
|------------------------|----|------|
| BOXES PER CASE | | 20 |
| WEIGHT PER CASE | lb | 24.5 |

BALLISTICS

| | | | | | | | |
|-------------------------|-------|--------|-------|-------|-------|-------|------|
| DISTANCE | y | MUZZLE | 100 | 200 | 300 | 400 | |
| VELOCITY | fps | 2,467 | 2,303 | 2,146 | 1,995 | 1,850 | |
| ENERGY | ft-lb | 1,919 | 1,672 | 1,452 | 1,255 | 1,079 | |
| DISTANCE | y | 50 | 100 | 200 | 300 | 400 | |
| POINTS OF IMPACT | in | -0.2 | 0.0 | -4.6 | -16.7 | -37.6 | |
| DISTANCE | y | 500 | 600 | 700 | 800 | 900 | 1000 |
| POINTS OF IMPACT | in | -69 | -112 | -169 | -242 | -336 | -454 |