30-06 SPRING.
TXRG 165 GRS SB3006XA

New generation lead free bullets Modern, highly efficient design incorporating a boat-tail base with a new, pointed tip for a flat trajectory and maximum retained energy. Blue plastic tip enhances expansion at all ranges while the solid copper construction maximizes weight retention.

PROPERTIES

BULLET	TYPE		TXRG
	WEIGHT	grs	165
	DIAMETER	in	0.308
	SECTIONAL DENSITY	lb/in²	0.248
	MATERIAL OF JACKET		-
BALLISTIC COEFFICIENT		G1	0.398
		G7	0.200
CARTRIDGE	LENGTH	in	3.339
POWER FACTOR ESTIMATED		kgr·fps	459.5
TEST BARREL LENGTH		in	23½
SUGGESTED USE			N/A
FEATURES			N/A

PACKAGING

BOXES PER CASE		12
WEIGHT PER CASE	lb	18.3

BALLISTICS

DISTANCE	y	MUZZLE	100	200	300	400
VELOCITY	fps	2,785	2,555	2,336	2,128	1,931
ENERGY	ft·lb	2,842	2,392	1,999	1,658	1,365

DISTANCE	y	50	100	200	300	400
POINTS OF IMPACT	in	-0.4	0.0	-3.3	-13.1	-30.5